



G.A.P. WaterGuard™ Self Adhered SBS Base Sheets

INSTALLATION INSTRUCTIONS

STORAGE

When storing and handling G.A.P. WaterGuard™ SA SBS Roof Membranes:

- Store rolls upright on pallets in dry ventilated indoor areas cooler than 100°F (38°C); do not store rolls on their sides
- Protect rolls from exposure to elements
- Stage the project as products are needed

BASIC INSTRUCTIONS:

- Low-Slope self-adhered roof systems are primarily designed for roofs at 2/12 pitch or less.
- When applying G.A.P. Roofing SA systems, ambient temperatures should be 40°F and rising.
- Do not install when water in any form exists.
- All roof deck application areas must have positive drainage, continuous support, and be structurally sound to support all load requirements of the roofing system.
- Prior to the application, be sure to properly prepare the substrate.
- In re-roofing applications, be sure to remove existing materials and obsolete penetrations and repair any voids or imperfections in the substrate.

Acceptable substrates include:

- Polyisocyanurate insulation standard facer
- DensDeck® Prime Roof Board or DuraGuard® Roof Board
- Securock® Gypsum-Fiber Reinforced Roof Board
- Primed concrete
- Plywood sheathing with bond breaker tape at all joints
- G.A.P. WaterGuard™ SA Base Sheet

Ensure installation of plies do not prevent or interfere with ventilation of the existing structure.

INSTALLING G.A.P. WATERGUARD SA BASE SHEETS:

Prior to installation, allow the membranes to relax in the sun for a minimum of 15 minutes.

- Start installation by cutting G.A.P. WaterGuard™ Base Sheet to suitable lengths
- Lay the membrane flat and align the membrane at the lowest edge of the roof
- Once the G.A.P. WaterGuard™ SA Base Sheet is in place, fold sheet in half to remove split release film at a 90° angle in a constant motion
- After both sides of release film are removed, position the next roll of G.A.P. WaterGuard™ SA Base Sheet by overlapping seams of the top sheet selvage edge a minimum of 6"
- Press the membrane with firm and even pressure
- Cut a 45° angle at the top corner of sheet, and at all build-up of joints such as T-joints and remove protective tape then press next membrane at seam
- Use hand roller at laps to ensure full adhesion
- Once G.A.P. WaterGuard™ SA Base Sheet layer is installed, be sure to run 80 lb. roller over the roof surface to ensure full adhesion



G.A.P. WaterGuard™ Self Adhered SBS Base Sheets

INSTALLATION INSTRUCTIONS

STANDARD ONE (1) YEAR LIMITED WARRANTY: G.A.P. Roofing, Inc. warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance for a period of one (1) year from the date of original purchase ("Warranty Period"). Should a manufacturing defect materially and adversely affect this product's performance, G.A.P. Roofing, Inc. shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover labor or installation costs, leaks, fastener penetrations or other holes in the membrane, exposure over 180 days, low slope roofs or materials not manufactured by G.A.P. Roofing, Inc., consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to G.A.P. Roofing, Inc., c/o Warranty Claims Department, 4444 Hunt Street, Pryor, OK. 74361.