



GAP No. 15 ASTM D226 PERF

4444 Hunt St. Pryor, OK 74361
Email: info@gaproofing.us
Phone: 918-825-5200
Fax: 918-825-5207

Company Website: GAProofing.us
Dealer Support: GAPdealers.com



WE OWN THE PAPER MILL

LOWER PRICING.
LOWER LEAD TIMES.
HIGHER QUALITY RAW MATERIALS.

GAP No. 15 ASTM D226 PERF

PRODUCT DESCRIPTION

GAP No. 15 ASTM D226 Perf is manufactured from organic felt and is saturated with saturant asphalt and perforated to allow venting of trapped air, vapor and gasses during application.

PRODUCT USE

GAP No. 15 ASTM PERF is underlayment used as an interplay felt for hot asphalt applied organic build-up roofing systems. It helps asphalt uniformity and adhesion between piles.

TECHNICAL DATA

ASTM D 226 Type 1

Width of Roll	18"
Roof Coverage per Roll	432 sq ft
Mass of Saturated Felt Roll	11.5 lbs/ 100 sq. ft
Mass of Saturant	6.2 lbs/ 100 Sq ft

Pallet Size 42" X 48" No. of Rolls per Pallet =25

MANUFACTURING LOCATIONS:

Pryor, OK