

## Product Data Sheet

## Product Description

<u>GMCraft</u> is asphalt saturated building paper, and is also described as a weather-resistive barrier, or moisture barrier in building codes. It is designed for installation behind stucco and other exterior wall claddings as a "secondary weather barrier". GMCraft contributes to the prevention of internal wall damage due to exterior moisture penetration or interior condensation.

## Products Standards

**<u>GMCraft 60</u>** is a "weather-restrictive barrier" as described in Section 1404.2 of the 2000 International Building Code® (IBC) and also qualifies as a "weather-resistive sheathing paper" as described in Section R703 of the 2000 International Residential Code TM (IRC).

<u>**GMCraft 60**</u> exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, and complies with Section 1402.1 of the 1997 Uniform Building (and subsequent UBC and CBC editions).

<u>GMCraft 60</u> has maintained ICC (formerly IBCO) Evaluation Reports, since October of 2000 and satisfies the test criteria for weather-resistive barriers (AC 38) dated July 2000. The outer surface is boldly printed with appropriate ICC ESR identification information. The current ESR 2376 is dated May 1, 2010.

<u>GMCraft 60</u> is evaluated by ongoing testing to insure that it meets or exceeds industry standards (including ASTM D-779-03, ASTM D-828). March 29, 2010 test results from an ICC Certified Testing Laboratory are listed below:

GMCraft 60	Test Method	Test Results
Water Vapor Transmission	ASTM E-96-00	<u>90 grams Pass</u>
Water Resistance	ASTM D-779	Exceeds 60 minutes
Tensile Strength	ASTM D-828	<u>MD 60 lb-f/in</u> <u>CD 44 lb-f/in</u>

**Physical Description** 

GMCraft 60 Single cover 240 SF (Roll Size: 40" x 72 lineal feet) GMCraft 60 Double covers 162 SF (Roll Size: 40" x 49 lineal feet – 2 layers)

> Manufactured by GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA. 93263 (661) 399 4324